



PR1600  
€124,95



PR1200  
€89,95



CR900  
€76,95



LR500S  
€36,95

Lens	Anti-schittering DuaLens	Anti-schittering DuaLens	Anti-schittering DuaLens	Curved Lens
Afstandsbediening	Draadloos	Bedraad	Bedraad	Bedraad (los verkocht)
HiLo Beam System (groot/klein licht)	Ja	Ja	-	-
Helderheid (lumen)	100 - 1600 lumen	100 - 1200 lumen	100 - 900 lumen	100 - 500 lumen
Aantal traps in lumen	Road: 800, 400, 200, 100, rapid flashing MTB: 1600, 800, 400	Road: 600, 400, 200, 100, rapid flashing MTB: 1200, 600, 300	900, 450, 200, 35, pulse flash, rapid flash + handmatig	500, 300 en 100 + rapid flashing
Max. afstand (meter)	150	142	105	120
Geschikt voor	donkere omgeving	donkere omgeving	onverlichte omgeving race	onverlichte omgeving tour
Mode memory	Ja	Ja	Ja	Ja
USB input	USB-C	Micro-USB	Micro-USB	Micro-USB
Oplaadbaar tijdens gebruik	Ja	-	-	Ja
USB output (powerbank)	Ja	Ja	-	-
Accu	Oplaadbaar Li-ion 6000mAh/3.7V	Oplaadbaar Li-ion 5200mAh/3.7V	Oplaadbaar Li-ion 3000mAh/3.7V	Oplaadbaar Li-ion 2200mAh/3.7V
Lumen Accuduur in uren	100 400 800 1600 20 4 2,5 1,4	100 400 600 1200 21 5 3,5 2	35 200 450 900 36 9 2,5 1,5	100 300 500 7,5 2,8 1,6
Display	Accuduur en mode indicator	Accuduur en mode indicator	Accuduur	-
Behuizing	Aluminium Mill Type III Hard Coat anodizing	Aluminium Mill Type III Hard Coat anodizing	Aluminium Mill Type III Hard Coat anodizing	Aluminium Mill Type III Hard Coat anodizing
Afmeting (mm) en gewicht	100(L)x48(B)x27(H) 220 gram	100(L)x48(B)x27(H) 213 gram	98(L)x30(B)x32(H) 115 gram	85(L)x36(B)x30(H) 119 gram
Waterdichtheid	IPX8 waterdicht (tot 1m onder water)	IPX8 waterdicht (tot 1m onder water)	IPX6 waterbestendig (bij stortbuien)	IPX6 waterbestendig (bij stortbuien)



CL06  
€33,95



TR50  
€29,95



TR20  
€19,95

LED	COB-led 4 sets met max. 50 lumen	COB-led 2 rijen met max. 50 lumen	COB-led met max. 20 lumen
Lichtsensoren	Ingebouwd	-	-
Remsensor	Ingebouwd	-	-
Stand Accuduur in uren	High Low flash pulse 8 18 30 12	High Low flash pulse 2,7 7,6 50 10	High Low flash pulse 1,5 5 10 11
Indicator	batterij indicator	batterij leeg en opladen	batterij leeg en opladen
Mode memory	Ja	Ja	Ja
USB input	USB-C	Micro-USB	Micro-USB
Montage	Quick-release met verstelbare band	Quick-release met rubberen bandjes	Quick-release met rubberen bandjes
Afmeting en gewicht	43(L)x22.5(B)x44(H) 31 gram	19(L)x35(B)x65(H) 41 gram	18(L)x22(B)x52(H) 15 gram
Waterdichtheid	IPX6 (waterbestendig)	IPX4 (spatwaterdicht)	IPX4 (spatwaterdicht)